

*** SUSPENSION UNIFORM INSPECTION GUIDELINES ***

Article Text

1987 Volkswagen Quantum/Quantum Syncro

For Volkswagen Technical Site

Copyright © 1998 Mitchell Repair Information Company, LLC

Sunday, March 19, 2000 12:40AM

ARTICLE BEGINNING

GENERAL INFORMATION

Steering & Suspension Systems - (Including Wheels & Tires)

All Makes & Models

Updated: January, 1997

MAP UNIFORM INSPECTION GENERAL GUIDELINES

OVERVIEW OF MOTORIST ASSURANCE PROGRAM

The Motorist Assurance Program (MAP) is the consumer outreach effort of the Automotive Maintenance and Repair Association, Inc. (AMRA). Participation in the Motorist Assurance Program is drawn from retailers, suppliers, independent repair facilities, vehicle manufacturers and industry associations.

The Motorist Assurance Program was established as an industry-wide effort to address concerns raised by regulators, the media and consumers questioning our ethics and methods of doing business. The automotive repair industry had been bombarded by months of negative stories in the media and scrutiny from state and federal regulators who focused on how the need for repairs is determined. MAP was formed as an industry response to this issue.

Our mission is to strengthen the relationship between the consumer and the auto repair industry. We produce materials that give motorists the information and encouragement to take responsibility for their vehicles - through proper, manufacturer-recommended, maintenance. We encourage participating service and repair shops (including franchisees and dealers) to adopt a Pledge to their Customers and the Motorist Assurance Program developed Standards of Service. All participating service providers have agreed to subscribe to this Pledge and to adhere to the promulgated Standards of Service which demonstrates to their customers that they are serious about customer satisfaction.

These Standards of Service require that an inspection of the vehicle's (problem) system be made according to industry guidelines. After learning that neither the car manufacturers nor any other source had complete guidelines, leading industry organizations, along with other industry participants banded together to address this challenging task. During the past two and a half years, they successfully developed industry inspection guidelines for the following systems: Exhaust, Brakes, ABS, Steering and Suspension, Engine Maintenance and Performance, HVAC, and Electrical systems. Guidelines for Drive Train and Transmission are currently being promulgated. Revisions to the inspection guidelines for Exhaust, Brakes/ABS and Steering and Suspension Systems, which were issued two years ago, are now being published for implementation beginning spring 1997. Participating shops utilize these Uniform Inspection Guidelines as part of the inspection process and for communicating their findings to their customers.

*** SUSPENSION UNIFORM INSPECTION GUIDELINES ***

Article Text (p. 2)

1987 Volkswagen Quantum/Quantum Syncro

For Volkswagen Technical Site

Copyright © 1998 Mitchell Repair Information Company, LLC

Sunday, March 19, 2000 12:40AM

The Motorist Assurance Program continues to work cooperatively and proactively with government agencies and consumer groups toward solutions that both benefit the customer and are mutually acceptable to both regulators and industry. We maintain the belief that industry must retain control over how we conduct our business, and we must be viewed as part of the solution and not part of the problem. Meetings with state and other government officials concerned with auto repair and/or consumer protection are conducted. Feedback from these representatives are brought back to members, and the program adjusted as needed.

To assure auto repair customers recourse if they were not satisfied with a repair transaction, the Motorist Assurance Program offers arbitration through MAP/BBB-CARE in cooperation with the Council of Better Business Bureaus and individual participating Bureaus. MAP "piloted" in Indianapolis and Pittsburgh during spring, 1996 - and publicized "roll-outs" in New Jersey, Detroit (MI), Chicago (IL) and Richmond (VA) were conducted. To put some "teeth" in the program, and accreditation requirement for shops was initiated. The requirements are stringent and a self-policing method has been incorporated which includes the "mystery shopping" of outlets. In addition, a committee of service providers had been working diligently developing standards for newspaper, television and Internet advertising.

We welcome you to join us as we continue our outreach ... with your support, both the automotive repair industry and your customers will reap the benefits. Please visit MAP at our Internet site: www.hunter.com/map.htm or contact us at:

808 17th Street, NW Suite 200

Washington, D.C. 20006

Ph. (202) 466-7050 Fax (202) 223-9569

OVERVIEW OF SERVICE REQUIREMENTS & SUGGESTIONS

It is MAP policy that all exhaust, brake, ABS, steering and suspension, wheel alignment, tires and wheels, driveline, engine performance and maintenance and heating, ventilation and air conditioning services be offered and performed under the guidelines and procedures specified in these sections.

Before any service is performed on a vehicle, an inspection of the appropriate system must be performed. The results of this inspection must be explained to the customer and documented on an inspection form. The condition of the vehicle and its components will indicate what services/part replacements may be required or suggested. In addition, suggestions may be made to satisfy the needs expressed by the customer.

This section lists the various parts and conditions that indicate required or suggested service or part replacement. Although this list is extensive, it is not inclusive. In addition to this list, a technician may make a suggestion. This suggestion must be based on substantial and informed experience or the vehicle manufacturer's recommended service interval.

*** SUSPENSION UNIFORM INSPECTION GUIDELINES ***

Article Text (p. 3)

1987 Volkswagen Quantum/Quantum Syncro

For Volkswagen Technical Site

Copyright © 1998 Mitchell Repair Information Company, LLC

Sunday, March 19, 2000 12:40AM

Some conditions indicate that service or part replacement is required because the part in question is no longer providing the function for which it is intended, does not meet a vehicle manufacturer's design specification or is missing.

- * Example: An exhaust pipe has corroded severely and has a hole in it through which exhaust gases are leaking. Replacement of the exhaust pipe in this case is required due to functional failure.
- * Example: A brake rotor has been worn to the point where it measures less than the vehicle manufacturer's specifications. Replacement of the rotor is required because it does not meet design specifications.

Some conditions indicate that a service or part replacement is suggested because the part is close to the end of its useful life or to address a customer's need, convenience or request. If a customer's vehicle has one of these conditions, the procedure may only be to suggest service.

- * Example: An exhaust pipe is rusted, corroded or weak, but no leaks are present. In this case, the exhaust pipe has not failed. However, there is evidence that the pipe may need replacement in the near future. Replacement of the pipe may be suggested for the customer's convenience in avoiding a future problem.
- * Example: The customer desires improved ride and/or handling, but the vehicle's shocks or struts have not failed. In this case, replacement may be suggested to satisfy the customer's wishes. In this case, replacement of the shocks or struts may not be sold as a requirement.

A customer, of course, has the choice of whether or not a shop will service his or her vehicle. He or she may decide not to follow some of your suggestions. When a customer declines to authorize a service or repair indicated in the MAP Uniform Inspection Guidelines as "required," a MAP shop may refuse service on that system, if proceeding with the work could create or continue an unsafe or unsatisfactory condition.

The following reasons may be used for required and suggested services. These codes are shown in the "Code" column of the Uniform Inspection Guidelines that follow.

PART REPLACEMENT CODE IDENTIFICATION

NOTE: Refer to the following tables for definitions of the codes listed in the condition/procedure tables for the specific components that may need to be replaced.

A - PART NO LONGER PERFORMS INTENDED PURPOSE

*** SUSPENSION UNIFORM INSPECTION GUIDELINES ***

Article Text (p. 4)

1987 Volkswagen Quantum/Quantum Syncro

For Volkswagen Technical Site

Copyright © 1998 Mitchell Repair Information Company, LLC

Sunday, March 19, 2000 12:40AM

UAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA;

3	Reasons to Require Repair	3	Reasons to Suggest Repair	3
3	or Replacement	3	or Replacement	3

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA-

3	A - Part no longer performs	3	1 - Part is close to the end of	3
3	intended purpose	3	its useful life (just above	3
3		3	discard specifications, or	3
3		3	weak; failure likely to	3
3		3	occur soon, etc.)	3

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAU

B - PART DOES NOT MEET DESIGN SPEC., REGARDLESS OF PERFORMANCE

UAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA;

3	Reasons to Require Repair	3	Reasons to Suggest Repair	3
3	or Replacement	3	or Replacement	3

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA-

3	B - Part does not meet a design	3	2 - To address a customer need,	3
3	specification (regardless	3	convenience, or request (to	3
3	of performance)	3	stiffen ride, enhance	3
3		3	performance, eliminate noise	3
3		3	etc.)	3

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAU

C - PART IS MISSING

UAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA;

3	Reasons to Require Repair	3	Reasons to Suggest Repair	3
3	or Replacement	3	or Replacement	3

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA-

3	C - Part is missing	3	3 - To comply with maintenance	3
3		3	recommended by the vehicle's	3
3		3	Original Equipment	3
3		3	Manufacturer (OEM)	3
3		3	4 - Technician's recommendation	3
3		3	based on substantial and	3
3		3	informed experience	3

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAU

STEERING & SUSPENSION

**SERVICE PROCEDURES REQUIRED & SUGGESTED FOR PROPER
VEHICLE OPERATION**

Steering and suspension are complex systems made up of a variety of interdependent components. For proper vehicle handling, ride, and tire wear, a thorough inspection is required whenever suspension work is being performed.

Conditions listed assume that the problem has been isolated to the specific component by proper testing procedures.

NOTE: When replacing steering and/or suspension components which may affect an alignment angle, you are required to check and adjust alignment as needed. Refer to the OEM specifications.

*** SUSPENSION UNIFORM INSPECTION GUIDELINES ***

Article Text (p. 5)

1987 Volkswagen Quantum/Quantum Syncro

For Volkswagen Technical Site

Copyright © 1998 Mitchell Repair Information Company, LLC

Sunday, March 19, 2000 12:40AM

CAUTION: DO NOT use ride height altering or load compensating components, such as variable rate springs and coil over shocks, on vehicles with height or load sensing proportioning valve-equipped braking systems, unless these components are original equipment.

AIR RIDE SUSPENSION

NOTE: Depending on the air suspension design, there are some aftermarket products available to eliminate the air ride suspension on certain vehicles. If the system has been eliminated with one of these products, then no service is suggested or required.

AIR RIDE SUSPENSION - AIR SHOCKS & AIR STRUTS

NOTE: This section covers the air spring portion of the air shock or strut. For dampening portion of shock or strut conditions and procedures, refer to the "Shock Absorbers, Strut Cartridges, and Strut Assemblies" section.

AIR RIDE SUSPENSION - AIR SHOCKS & AIR STRUTS

Condition				Code	Procedure
Inner fabric of air bag				A	Require replacement.
damaged					
Leaking				A	Require repair or replacement.
Outer covering of air bag				A,1	Suggest replacement.
is cracked to the extent					
that inner fabric of air					
bag is visible					

AIR RIDE SUSPENSION - AIR SPRING VALVES

AIR RIDE SUSPENSION - AIR SPRING VALVES

Condition				Code	Procedure
Attaching hardware				A	Require replacement of incorrect
incorrect					part.
Attaching hardware loose				A	Require repair or replacement of
					loose part.
Attaching hardware missing				C	Require replacement of missing
					part.

*** SUSPENSION UNIFORM INSPECTION GUIDELINES ***

Article Text (p. 6)

1987 Volkswagen Quantum/Quantum Syncro

For Volkswagen Technical Site

Copyright © 1998 Mitchell Repair Information Company, LLC

Sunday, March 19, 2000 12:40AM

Attaching hardware threads	3	A	3	Require repair or replacement of
damaged	3		3	part with damaged threads.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA				
Attaching hardware threads	3	A	3	Require replacement of part with
stripped (threads missing)	3		3	stripped threads.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA				
Blocked	3	A	3	Require repair or replacement.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA				
Connector bent	3	A	3	Require repair or replacement.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA				
Connector broken	3	A	3	Require replacement.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA				
Connector loose	3	A	3	Require repair or replacement.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA				
Inoperative	3	A	3	Require repair or replacement.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA				
Leaking	3	A	3	Require repair or replacement.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA				
Restricted	3	A	3	Require repair or replacement.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA				

AIR RIDE SUSPENSION - AIR SPRINGS

AIR RIDE SUSPENSION - AIR SPRINGS				
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA				
Condition	3	Code	3	Procedure
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA				
Attaching hardware broken	3	A	3	Require replacement of broken
	3		3	part.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA				
Attaching hardware	3	A	3	Require replacement of incorrect
incorrect	3		3	part.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA				
Attaching hardware loose	3	A	3	Require repair or replacement of
	3		3	loose part.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA				
Attaching hardware missing	3	C	3	Require replacement of missing
	3		3	part.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA				
Attaching hardware threads	3	A	3	Require repair or replacement of
damaged	3		3	part with damaged threads.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA				
Attaching hardware threads	3	A	3	Require replacement of part with
stripped (threads missing)	3		3	stripped threads.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA				
Collar cracked	3	A	3	Require replacement.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA				
End cap cracked	3	A	3	Require replacement.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA				
Inner fabric of bag damaged	3	A	3	Require replacement.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA				
Leaking	3	A	3	Require repair or replacement.

*** SUSPENSION UNIFORM INSPECTION GUIDELINES ***

Article Text (p. 7)

1987 Volkswagen Quantum/Quantum Syncro

For Volkswagen Technical Site

Copyright © 1998 Mitchell Repair Information Company, LLC

Sunday, March 19, 2000 12:40AM

Outer covering of air bag 3 A,1 3 Suggest replacement.

is cracked to the extent 3 3

that inner fabric of air 3 3

bag is visible 3 3

Piston cracked 3 A 3 Require replacement.

AIR RIDE SUSPENSION - COMPRESSORS

AIR RIDE SUSPENSION - COMPRESSORS

Condition 3 Code 3 Procedure

Attaching hardware bent 3 B 3 Require repair or replacement of

bent part. 3 3

Attaching hardware broken 3 A 3 Require replacement of broken

part. 3 3

Attaching hardware loose 3 A 3 Require repair or replacement of

loose part. 3 3

Attaching hardware missing 3 C 3 Require replacement of missing

part. 3 3

Attaching hardware threads 3 A 3 Require repair or replacement of

damaged 3 3 part with damaged threads.

Attaching hardware threads 3 A 3 Require replacement of part with

stripped (threads missing) 3 3 stripped threads.

Connector bent 3 A 3 Require repair or replacement.

Connector broken 3 A 3 Require replacement.

Connector loose 3 A 3 Require repair or replacement.

Does not build pressure 3 A 3 Further inspection required.

3 3 See note (1) below.

Excessive run time 3 B 3 Further inspection required.

3 3 See note (2) below.

Inoperative 3 A 3 Require replacement.

Leaking 3 A 3 Require repair or replacement.

Missing 3 C 3 Require replacement.

NOTE: (1) If failure to build pressure is traced to the compressor,

*** SUSPENSION UNIFORM INSPECTION GUIDELINES ***

Article Text (p. 8)

1987 Volkswagen Quantum/Quantum Syncro

For Volkswagen Technical Site

Copyright © 1998 Mitchell Repair Information Company, LLC

Sunday, March 19, 2000 12:40AM

require replacement.

- (2) If excessive run time is traced to the compressor, require replacement.

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

AIR RIDE SUSPENSION - HEIGHT SENSORS

AIR RIDE SUSPENSION - HEIGHT SENSORS

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Condition	3	Code	3	Procedure
-----------	---	------	---	-----------

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Attaching hardware bent	3	B	3	Require repair or replacement of bent part.
-------------------------	---	---	---	---------------------------------------------

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Attaching hardware broken	3	A	3	Require replacement of broken part.
---------------------------	---	---	---	-------------------------------------

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Attaching hardware corroded affecting structural integrity	3	A	3	Require replacement of corroded part.
------------------------------------------------------------	---	---	---	---------------------------------------

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Attaching hardware loose	3	A	3	Require repair or replacement of loose part.
--------------------------	---	---	---	----------------------------------------------

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Attaching hardware missing	3	C	3	Require replacement of missing part.
----------------------------	---	---	---	--------------------------------------

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Attaching hardware threads damaged	3	A	3	Require repair or replacement of part with damaged threads.
------------------------------------	---	---	---	-------------------------------------------------------------

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Attaching hardware threads stripped (threads missing)	3		3	Require replacement of part with stripped threads.
-------------------------------------------------------	---	--	---	----------------------------------------------------

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Dust boot missing	3	B,2	3	Suggest replacement. See note (1).
-------------------	---	-----	---	------------------------------------

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Dust boot split	3	B,2	3	Suggest replacement. See note (1).
-----------------	---	-----	---	------------------------------------

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Dust boot torn	3	B,2	3	Suggest replacement. See note (1).
----------------	---	-----	---	------------------------------------

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Housing cracked	3	A	3	Require replacement.
-----------------	---	---	---	----------------------

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Lead routing incorrect	3	B	3	Require re-routing according to vehicle manufacturer's specs.
------------------------	---	---	---	---------------------------------------------------------------

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Loose	3	B	3	Require adjustment to vehicle manufacturer's specifications.
-------	---	---	---	--------------------------------------------------------------

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Missing	3	C	3	Require replacement.
---------	---	---	---	----------------------

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Output signal incorrect	3	A	3	Require repair or replacement.
-------------------------	---	---	---	--------------------------------

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Wire lead damaged	3	A	3	Require repair or replacement.
-------------------	---	---	---	--------------------------------

*** SUSPENSION UNIFORM INSPECTION GUIDELINES ***

Article Text (p. 10)

1987 Volkswagen Quantum/Quantum Syncro

For Volkswagen Technical Site

Copyright © 1998 Mitchell Repair Information Company, LLC

Sunday, March 19, 2000 12:40AM

Condition	3	Code	3	Procedure
Broken	3	A	3	Require replacement.
Missing	3	C	3	Require replacement.
Output signal incorrect	3	A	3	Require replacement.

AIR RIDE SUSPENSION - TORSION SPRINGS (COUNTER BALANCING)

AIR RIDE SUSPENSION - TORSION SPRINGS (COUNTER BALANCING)				
Condition	3	Code	3	Procedure
Attaching hardware bent	3	B	3	Require repair or replacement of bent part.
Attaching hardware broken	3	A	3	Require replacement of broken part.
Attaching hardware incorrect	3	A	3	Require replacement of incorrect part.
Attaching hardware loose	3	A	3	Require repair or replacement of loose part.
Attaching hardware missing	3	C	3	Require replacement of missing part.
Attaching hardware threads damaged	3	A	3	Require repair or replacement of part with damaged threads.
Attaching hardware threads stripped (threads missing)	3	A	3	Require replacement of part with stripped threads.
Broken	3	A	3	Require replacement.
Missing	3	C	3	Require replacement.

AIR RIDE SUSPENSION - TUBING

AIR RIDE SUSPENSION - TUBING				
Condition	3	Code	3	Procedure
Attaching hardware incorrect	3	A	3	Require replacement of incorrect part.
Attaching hardware loose	3	A	3	Require repair or replacement of loose part.

*** SUSPENSION UNIFORM INSPECTION GUIDELINES ***

Article Text (p. 11)

1987 Volkswagen Quantum/Quantum Syncro

For Volkswagen Technical Site

Copyright © 1998 Mitchell Repair Information Company, LLC

Sunday, March 19, 2000 12:40AM

```

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
Attaching hardware missing      3   C   3   Require replacement of missing
                                   3   3   part.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
Blocked                          3   A   3   Require repair or replacement.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
Fitting incorrect               3   B   3   Require replacement.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
Leaking                          3   A   3   Require repair or replacement.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
Line type incorrect             3   B   3   Require replacement.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
Missing                         3   C   3   Require replacement.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
Restricted                      3   A   3   Require repair or replacement.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
Routed incorrectly              3   B   3   Require routing correction.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

```

AIR RIDE SUSPENSION - WARNING LAMPS

AIR RIDE SUSPENSION - WARNING LAMPS

```

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
Condition                        3   Code 3   Procedure
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
Bulb burned out                 3   A   3   Require replacement.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
Warning light does not come     3       3
on during bulb check           3       3
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
Warning light flashes           3       3
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
Warning light is intermittent  3       3 Further inspection required to
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
Warning light stays on after    3       3 determine cause.
initial bulb check              3       3
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

```

AIR RIDE SUSPENSION - WIRING HARNESSSES

AIR RIDE SUSPENSION - WIRING HARNESSSES

```

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
Condition                        3   Code 3   Procedure
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
Connector bent                  3   A   3
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
Connector broken                3   A   3
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
Connector loose                 3   A   3 Require repair or replacement.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
Damaged (cut, burned, or        3   A   3
chafed)                         3       3

```

Sunday, March 19, 2000 12:40AM

Condition	Code	Procedure
-----------	------	-----------

Sunday, March 19, 2000 12:40AM

freeing:

*** SUSPENSION UNIFORM INSPECTION GUIDELINES ***

Article Text (p. 14)

1987 Volkswagen Quantum/Quantum Syncro

For Volkswagen Technical Site

Copyright © 1998 Mitchell Repair Information Company, LLC

Sunday, March 19, 2000 12:40AM

Greaseable ball joint will 3 B,2 3 Suggest replacement of grease
not take grease 3 3 fitting. See note (5) below.
AAAAAA
Nut on ball joint loose 3 A 3 Require repair or replacement.
3 3 See note (6) below.
AAAAAA
Pre-load adjustment 3 B 3 Require repair or replacement.
incorrect 3 3
AAAAAA
Seized 3 A 3 Require replacement.
AAAAAA
Stud bent 3 B 3 Require replacement. See note (7).
AAAAAA
Stud broken 3 A 3 Require replacement. See note (7).
AAAAAA
Threads damaged 3 A 3 Require repair or replacement.
AAAAAA
Threads stripped (threads 3 A 3 Require replacement. See note (7).
missing) 3 3
AAAAAA
Wear exceeds manufacturer's 3 B 3 Require replacement.
specifications 3 3
AAAAAA

NOTE: (1) If greaseable, grease ball joint. If problem persists or
joint is non-greaseable, require replacement.
(2) Cracked grease boot will allow contaminants to enter the
ball joint and will accelerate wear.
(3) Lack of grease boot will allow contaminants to enter the
ball joint and will accelerate wear.
(4) Torn grease boot will allow contaminants to enter the ball
joint and will accelerate wear.
(5) If the greaseable ball joint still will not take grease
after replacing the grease fitting, suggest replacement of
ball joint.
(6) Check for bent stud or damaged taper hole.
(7) Check for damaged taper hole.

AAAAAA

BUSHINGS

BUSHINGS

AAAAAA
Condition 3 Code 3 Procedure
AAAAAA
Attaching hardware bent 3 B 3 Require repair or replacement of
3 3 bent part if available; otherwise,
3 3 replace bushing.
AAAAAA
Attaching hardware broken 3 A 3 Require replacement of broken part
3 3 if available; otherwise, replace
3 3 bushing.
AAAAAA

* SUSPENSION UNIFORM INSPECTION GUIDELINES *

Article Text (p. 15)

1987 Volkswagen Quantum/Quantum Syncro

For Volkswagen Technical Site

Copyright © 1998 Mitchell Repair Information Company, LLC

Sunday, March 19, 2000 12:40AM

Attaching hardware corroded	3	A	3	Require replacement of corroded part if available; otherwise, replace bushing.
Attaching hardware incorrect	3	A	3	Require replacement of incorrect part if available; otherwise, replace bushing.
Attaching hardware loose	3	A	3	Require repair or replacement of loose part if available; otherwise, replace bushing.
Attaching hardware missing	3	C	3	Require replacement of missing part if available; otherwise, replace bushing.
Attaching hardware threads damaged	3	A	3	Require repair or replacement of part with damaged threads if available; otherwise, replace bushing.
Attaching hardware threads stripped (threads missing)	3	A	3	Require replacement of part with stripped threads if available; otherwise, replace bushing.
Binding	3	A	3	Require repair or replacement.
Deteriorated, affecting performance	3	A	3	Require repair or replacement.
Distorted, affecting performance	3	A	3	Require repair or replacement.
Leaking (fluid-filled type)	3	A	3	Require replacement.
Missing	3	A	3	Require replacement.
Noisy	3	B,2	3	Further inspection required. See note (1) and caution below.
Rubber separating from internal metal sleeve on bonded bushing	3	A	3	Require replacement.
Seized	3	A	3	Require replacement.
Shifted (out of position)	3	B	3	Require repair or replacement.
Split	3	A	3	Require replacement.
Surface cracking (weather-checked)	3		3	No service suggested or required.

*** SUSPENSION UNIFORM INSPECTION GUIDELINES ***

Article Text (p. 16)

1987 Volkswagen Quantum/Quantum Syncro

For Volkswagen Technical Site

Copyright © 1998 Mitchell Repair Information Company, LLC

Sunday, March 19, 2000 12:40AM

NOTE: (1) If noise isolated to bushing, suggest repair or replacement.

CAUTION: Use only approved lubricant on rubber bushings. Petroleum-based lubricants may damage rubber bushings.

CENTER LINKS

CENTER LINKS

Condition	3	Code	3	Procedure
Attaching hardware incorrect	3	A	3	Require replacement of incorrect part, if available; otherwise, replace center link.
Attaching hardware loose	3	A	3	Require repair or replacement of loose part, if available; otherwise, replace center link.
Attaching hardware missing	3	C	3	Require replacement of missing part, if available; otherwise, replace center link.
Attaching hardware threads damaged	3	A	3	Require repair or replacement of part with damaged threads, if available; otherwise, replace center link.
Attaching hardware threads stripped (threads missing)	3	A	3	Require replacement of part with stripped threads, if available; otherwise, replace center link.
Bent	3	B	3	Require replacement.
Binding	3	A	3	Further inspection required. See note (1) below.
Grease boot cracked	3	B,2	3	Suggest replacement. See note (2).
Grease boot missing	3	B,2	3	Suggest replacement. See note (3).
Grease boot torn	3	B,2	3	Suggest replacement. See note (4).
Grease fitting broken	3	A	3	Require replacement of grease fitting.
Grease fitting missing	3	C	3	Require replacement of grease fitting.
Grease fitting won't seal	3	A	3	Require replacement of grease

*** SUSPENSION UNIFORM INSPECTION GUIDELINES ***

Article Text (p. 17)

1987 Volkswagen Quantum/Quantum Syncro

For Volkswagen Technical Site

Copyright © 1998 Mitchell Repair Information Company, LLC

Sunday, March 19, 2000 12:40AM

3 3 fitting.

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Grease seal missing 3 B,2 3 Suggest replacement. See note (5).

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Grease seal torn 3 B,2 3 Suggest replacement. See note (6).

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Looseness (perceptible 3 A,1 3 Suggest replacement. See note (7).

horizontal movement) 3 3

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

CAUTION: DO NOT use pliers or pry bar to check ball and socket

movement. Use only moderate hand pressure.

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Looseness that is excessive 3 B 3 Require replacement. See notes (8)

3 3 and (9), caution below.

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

CAUTION: DO NOT use pliers or pry bar to check ball and socket

movement. Use only moderate hand pressure.

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Seized 3 A 3 Require replacement.

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Stud bent 3 B 3 Require replacement. See note (10)

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Stud broken 3 A 3 Require replacement. See note (10)

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Stud loose in taper hole 3 A 3 Require repair or replacement.

3 3 See note (10) below.

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Taper hole elongated 3 A 3 Require replacement. See note (11)

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Threads damaged 3 A 3 Require repair or replacement.

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Threads stripped (threads 3 A 3 Require replacement. See note (10)

missing) 3 3

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Wear exceeds manufacturer's 3 B 3 Require replacement.

specifications 3 3

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

NOTE: (1) If greaseable, grease joint. If problem persists or joint is non-greaseable, require replacement.

(2) Cracked grease boot will allow contaminants to enter the joint and will accelerate wear.

(3) Lack of grease boot will allow contaminants to enter the joint and will accelerate wear.

(4) Torn grease boot will allow contaminants to enter the joint and will accelerate wear.

(5) Lack of grease seal will allow contaminants to enter the joint and will accelerate wear.

(6) Torn grease seal will allow contaminants to enter the joint and will accelerate wear.

(7) If manufacturer's procedures for inspection exist, use those procedures; otherwise, use an approved inspection method such as the dry park check.

*** SUSPENSION UNIFORM INSPECTION GUIDELINES ***

Article Text (p. 18)

1987 Volkswagen Quantum/Quantum Syncro

For Volkswagen Technical Site

Copyright © 1998 Mitchell Repair Information Company, LLC

Sunday, March 19, 2000 12:40AM

- (8) Excessive looseness is defined as being significant enough to affect vehicle handling or structural integrity.
- (9) If manufacturer's procedures for inspection exist, use those procedures; otherwise, use an approved inspection method such as the dry park check.
- (10) Check for damaged taper hole.
- (11) Check for damaged stud.

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

CONTROL ARM SHAFTS

CONTROL ARM SHAFTS

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Condition	3	Code	3	Procedure
Attaching hardware broken	3	A	3	Require replacement of broken part, if available; otherwise, replace shaft.
Attaching hardware loose	3	A	3	Require repair or replacement of loose part, if available; otherwise, replace shaft.
Attaching hardware missing	3	C	3	Require replacement of missing part, if available; otherwise, replace shaft.
Attaching hardware threads damaged	3	A	3	Require repair or replacement of part with damaged threads, if available; otherwise, replace shaft.
Attaching hardware threads stripped (threads missing)	3	A	3	Require replacement of part with stripped threads, if available; otherwise, replace shaft.
Bent	3	B	3	Require replacement.
Shaft bushing surface undersized (worn)	3	B	3	Require replacement.
Threads damaged	3	A	3	Require repair or replacement.
Threads stripped (threads missing)	3	A	3	Require replacement.

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

CONTROL ARMS

CONTROL ARMS

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Condition	3	Code	3	Procedure
Attaching hardware bent	3	B	3	Require repair or replacement of bent part, if available; otherwise, replace control arm.
Attaching hardware broken	3	A	3	Require replacement of broken part, if available; otherwise, replace control arm.

*** SUSPENSION UNIFORM INSPECTION GUIDELINES ***

Article Text (p. 19)

1987 Volkswagen Quantum/Quantum Syncro

For Volkswagen Technical Site

Copyright © 1998 Mitchell Repair Information Company, LLC

Sunday, March 19, 2000 12:40AM

```

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
Attaching hardware corroded3 A 3 Require replacement of corroded
affecting structural 3 3 part, if available; otherwise,
integrity 3 3 replace control arm.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
Attaching hardware 3 A 3 Require replacement of incorrect
incorrect 3 3 part, if available; otherwise,
3 3 replace control arm.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
Attaching hardware loose 3 A 3 Require repair or replacement of
3 3 loose part, if available;
3 3 otherwise, replace control arm.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
Attaching hardware missing 3 C 3 Require replacement of missing
3 3 part, if available; otherwise,
3 3 replace control arm.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
Attaching hardware threads 3 A 3 Require repair or replacement of
damaged 3 3 part with damaged threads, if
3 3 available; otherwise, replace
3 3 control arm.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
Attaching hardware threads 3 A 3 Require replacement of part with
stripped (threads missing)3 3 stripped threads, if available;
3 3 otherwise, replace control arm.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
Bent 3 B 3 Require replacement.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
Bushings hole oversized 3 B 3 Require replacement.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
Ball joint hole oversized 3 B 3 Further inspection required.
(loose interference or 3 3 See note (1) below.
press fit) 3 3
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
Corroded, affecting 3 A 3 Require replacement.
structural integrity 3 3
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
Holes distorted 3 A 3 Require replacement.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
Threads damaged 3 A 3 Require repair or replacement.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
Threads stripped (threads 3 A 3 Require replacement.
missing) 3 3
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
NOTE: (1) If oversized ball joint is available, require replacement
of ball joint. If oversized ball joint is not available,
require replacement of control arm.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

```

DRAG LINKS

DRAG LINKS

*** SUSPENSION UNIFORM INSPECTION GUIDELINES ***

Article Text (p. 20)

1987 Volkswagen Quantum/Quantum Syncro

For Volkswagen Technical Site

Copyright © 1998 Mitchell Repair Information Company, LLC

Sunday, March 19, 2000 12:40AM

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA			
Condition	3	Code	3 Procedure
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA			
Attaching hardware incorrect	3	A	3 Require replacement of incorrect part, if available; otherwise, replace drag link.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA			
Attaching hardware loose	3	A	3 Require repair or replacement of loose part, if available; otherwise, replace drag link.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA			
Attaching hardware missing	3	C	3 Require replacement of missing part, if available; otherwise, replace drag link.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA			
Attaching hardware threads damaged	3	A	3 Require repair or replacement of part with damaged threads, if available; otherwise, replace drag link.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA			
Attaching hardware threads stripped (threads missing)	3	A	3 Require replacement of part with stripped threads, if available; otherwise, replace drag link.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA			
Bent	3	B	3 Require replacement.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA			
Binding	3	A	3 Further inspection required. See note (1) below.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA			
Grease boot cracked	3	B,2	3 Suggest replacement. See note (2).
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA			
Grease boot missing	3	B,2	3 Suggest replacement. See note (3).
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA			
Grease boot torn	3	B,2	3 Suggest replacement. See note (4).
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA			
Grease fitting broken	3	A	3 Require replacement of grease fitting.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA			
Grease fitting missing	3	C	3 Require replacement of grease fitting.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA			
Grease fitting won't seal	3	A	3 Require replacement of grease fitting.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA			
Grease seal missing	3	B,2	3 Suggest replacement. See note (5).
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA			
Grease seal torn	3	B,2	3 Suggest replacement. See note (4).
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA			
Looseness (perceptible horizontal movement)	3	A,1	3 Suggest replacement. See note (6).
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA			
CAUTION: DO NOT use pliers or pry bar to check ball and socket			

*** SUSPENSION UNIFORM INSPECTION GUIDELINES ***

Article Text (p. 21)

1987 Volkswagen Quantum/Quantum Syncro

For Volkswagen Technical Site

Copyright © 1998 Mitchell Repair Information Company, LLC

Sunday, March 19, 2000 12:40AM

movement. Use only moderate hand pressure.

Looseness that is excessive³ B ³ Require replacement. See notes (6)

³ and (7), caution below.

CAUTION: DO NOT use pliers or pry bar to check ball and socket

movement. Use only moderate hand pressure.

Seized ³ A ³ Require replacement.

Stud bent ³ B ³ Require replacement. See note (8).

Stud broken ³ A ³ Require replacement. See note (8).

Stud loose in taper hole ³ A ³ Require repair or replacement.

³ See note (8) below.

Taper hole elongated ³ A ³ Require replacement. See note (9).

Threads damaged ³ A ³ Require repair or replacement.

Threads stripped (threads ³ A ³ Require replacement. See note (8).

missing) ³ ³

Wear exceeds manufacturer's³ B ³ Require replacement.

specifications ³ ³

NOTE: (1) If greaseable, grease joint. If problem persists or joint is non-greaseable, require replacement.

(2) Cracked grease boot will allow contaminants to enter the joint and will accelerate wear.

(3) Lack of grease boot will allow contaminants to enter the joint and will accelerate wear.

(4) Torn grease boot will allow contaminants to enter the joint and will accelerate wear.

(5) Missing grease seal will allow contaminants to enter the joint and will accelerate wear.

(6) If manufacturer's procedures for inspection exist, use those procedures; otherwise, use an approved inspection method such as the dry park check.

(7) Excessive looseness is defined as being significant enough to affect vehicle handling or structural integrity.

(8) Check for damaged taper hole.

(9) Check for damaged stud.

ELECTRONIC RIDE CONTROL SHOCKS & STRUTS

NOTE: This section covers the electronic damping control portion of the electronic shock or strut. For dampening portion of shock or strut conditions and procedures, refer to the "Shock Absorbers, Strut Cartridges, and Strut Assemblies" section.

*** SUSPENSION UNIFORM INSPECTION GUIDELINES ***

Article Text (p. 22)

1987 Volkswagen Quantum/Quantum Syncro

For Volkswagen Technical Site

Copyright © 1998 Mitchell Repair Information Company, LLC

Sunday, March 19, 2000 12:40AM

ELECTRONIC RIDE CONTROL SHOCKS & STRUTS

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA			
Condition	3	Code 3	Procedure
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA			
Connector bent	3	A 3	Require repair or replacement.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA			
Connector broken	3	A 3	Require repair or replacement.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA			
Connector loose	3	A 3	Require repair or replacement.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA			
Electronic valve control inoperative	3	B,2 3	Suggest replacement. See note (1).
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA			
Terminal bent	3	A 3	Require repair or replacement.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA			
Terminal broken	3	A 3	Require repair or replacement.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA			
Terminal corroded	3	A 3	Require repair or replacement.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA			
Terminal loose	3	A 3	Require repair or replacement.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA			
NOTE: (1) It is acceptable to replace with a non-electronically controlled unit, where available.			
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA			

IDLER ARMS

IDLER ARMS

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA			
Condition	3	Code 3	Procedure
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA			
Attaching hardware broken	3	A 3	Require replacement of broken
	3		part, if available; otherwise,
	3		replace idler arm.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA			
Attaching hardware incorrect	3	A 3	Require replacement of incorrect
	3		part, if available; otherwise,
	3		replace idler arm.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA			
Attaching hardware loose	3	A 3	Require repair or replacement of
	3		loose part, if available;
	3		otherwise, replace idler arm.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA			
Attaching hardware missing	3	C 3	Require replacement of missing
	3		part, if available; otherwise,
	3		replace idler arm.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA			
Attaching hardware threads damaged	3	A 3	Require repair or replacement of
	3		part with damaged threads, if
	3		available; otherwise, replace
	3		idler arm.

*** SUSPENSION UNIFORM INSPECTION GUIDELINES ***

Article Text (p. 23)

1987 Volkswagen Quantum/Quantum Syncro

For Volkswagen Technical Site

Copyright © 1998 Mitchell Repair Information Company, LLC

Sunday, March 19, 2000 12:40AM

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Attaching hardware threads ³ A ³ Require replacement of part with
stripped (threads missing)³ ³ stripped threads, if available;
³ ³ otherwise, replace idler arm.

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Binding ³ A ³ Further inspection required.
³ ³ See note (1) below.

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Grease boot cracked ³ B,2 ³ Suggest replacement. See note (2).

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Grease boot missing ³ B,2 ³ Suggest replacement. See note (3).

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Grease boot torn ³ B,2 ³ Suggest replacement. See note (4).

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Grease fitting broken ³ A ³ Require replacement of grease
³ ³ fitting.

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Grease fitting missing ³ C ³ Require replacement of grease
³ ³ fitting.

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Grease fitting won't seal ³ A ³ Require replacement of seal.

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Grease seal missing ³ B,2 ³ Suggest replacement. See note (5).

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Grease seal torn ³ B,2 ³ Suggest replacement. See note (4).

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Greaseable joint will not ³ B,2 ³ Suggest replacement of grease
take grease ³ ³ fitting. See note (6) below.

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Looseness at frame bracket ³ B ³ Require repair or replacement.
end ³ ³ See notes (7) and (8) below.

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Looseness at link end ³ A,1 ³ Suggest replacement. See note (7).
(perceptible horizontal ³ ³
movement) ³ ³

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

CAUTION: DO NOT use pliers or pry bar to check ball and socket
movement. Use only moderate hand pressure.

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Looseness at link end that ³ B ³ Require replacement. See notes (7)
is excessive ³ ³ and (9) and caution below.

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

CAUTION: DO NOT use pliers or pry bar to check ball and socket
movement. Use only moderate hand pressure.

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Mounted out of position ³ B ³ Require repositioning.
(center link not parallel)³ ³

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Nut on stud loose ³ A ³ Require repair or replacement.
³ ³ See note (10) below.

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Seized ³ A ³ Require replacement.

*** SUSPENSION UNIFORM INSPECTION GUIDELINES ***

Article Text (p. 24)

1987 Volkswagen Quantum/Quantum Syncro

For Volkswagen Technical Site

Copyright © 1998 Mitchell Repair Information Company, LLC

Sunday, March 19, 2000 12:40AM

```

Stud bent          3 B 3 Require replacement. See note (11)
Stud broken        3 A 3 Require replacement. See note (11)
Taper hole elongated 3 A 3 Require replacement. See note (12)
Threads damaged     3 A 3 Require repair or replacement.
Threads stripped (threads 3 A 3 Require replacement. See note (11)
missing)           3 3
Wear exceeds manufacturer's 3 B 3 Require replacement.
specifications     3 3

```

- NOTE: (1) If greaseable, grease joint. If problem persists or joint is non-greaseable, require replacement.
- (2) Cracked grease boot will allow contaminants to enter joint and will accelerate wear.
- (3) Lack of grease boot will allow contaminants to enter joint and will accelerate wear.
- (4) Torn grease boot will allow contaminants to enter joint and will accelerate wear.
- (5) Missing grease seal will allow contaminants to enter joint and will accelerate wear.
- (6) If greaseable joint will not take grease after replacing the grease fitting, suggest replacement of idler arm.
- (7) If manufacturer's procedures and specifications exist, use those procedures and specifications; otherwise, use an approved inspection method such as the dry park check.
- (8) Looseness is defined as movement that creates excessive toe change.
- (9) Excessive looseness is defined as significant enough to affect vehicle handling or structural integrity.
- (10) Check for bent stud or damaged taper hole.
- (11) Check for damaged taper hole.
- (12) Check for damaged stud.

KING PINS

You are not required to replace king pins in axle sets. However, when replacing a king pin due to wear exceeding manufacturer's specifications, you may suggest replacement of the other king pin on the axle if its measurement shows it is close to the end of its useful life.

KING PINS

```

Condition          3 Code 3 Procedure
Bearing balls pitted 3 A 3 Require replacement.

```


*** SUSPENSION UNIFORM INSPECTION GUIDELINES ***

Article Text (p. 25)

1987 Volkswagen Quantum/Quantum Syncro

For Volkswagen Technical Site

Copyright © 1998 Mitchell Repair Information Company, LLC

Sunday, March 19, 2000 12:40AM

```

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
Bearing balls worn          3 A 3 Require replacement.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
Bearing races pitted       3 A 3 Require replacement.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
Bearing races worn         3 A 3 Require replacement.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
Bearing rollers pitted     3 A 3 Require replacement.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
Bearing rollers worn       3 A 3 Require replacement.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
Bearing seal bent          3 B,2 3
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA - Suggest replacement of seal or
Bearing seal missing        3 B,2 3 bearing.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA -
Bearing seal torn           3 B,2 3
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
Binding                     3 A 3 Require repair or replacement of
                           3 3 affected parts.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
End caps missing           3 C 3 Require replacement of missing
                           3 3 part, if available; otherwise,
                           3 3 replace king pin.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
End play exceeds           3 B 3 Require repair.
specifications             3 3
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
Grease fitting broken      3 A 3
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA -
Grease fitting missing     3 C 3 Require replacement of grease
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA - fitting.
Grease fitting won't seal  3 A 3
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
Locating pins missing      3 C 3 Require replacement of missing
                           3 3 part, if available; otherwise,
                           3 3 replace king pin.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
Looseness exceeds          3 B 3 Require replacement of worn parts.
manufacturer's specs       3 3
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
Seized                     3 A 3 Require replacement.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
Threads damaged            3 A 3 Require repair or replacement.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
Threads stripped (threads  3 A 3 Require replacement.
missing)                   3 3
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
Will not take grease       3 B,2 3 Suggest replacement of grease
                           3 3 fitting. See note (1) below.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

```

NOTE: (1) If king pin will not take grease after replacement of grease fitting, suggest replacement of king pin.

SEE PAGE (6) BELOW:

*** SUSPENSION UNIFORM INSPECTION GUIDELINES ***

Article Text (p. 27)

1987 Volkswagen Quantum/Quantum Syncro

For Volkswagen Technical Site

Copyright © 1998 Mitchell Repair Information Company, LLC

Sunday, March 19, 2000 12:40AM

Looseness (perceptible horizontal movement) 3 A,1 3 Suggest replacement. See note (7)

CAUTION: DO NOT use pliers or pry bar to check ball and socket

movement. Use only moderate hand pressure.

Looseness that is excessive 3 B 3 Require replacement. See notes (7) and (8), caution below.

CAUTION: DO NOT use pliers or pry bar to check ball and socket movement. Use only moderate hand pressure.

Nut on stud loose 3 A 3 Require repair or replacement. See note (9) below.

Seized 3 A 3 Require replacement.

Splines damaged 3 A 3 Require repair or replacement.

Splines stripped (splines missing) 3 A 3 Require replacement.

Stud bent 3 B 3 Require replacement. See note (10)

Stud broken 3 A 3 Require replacement. See note (10)

Stud loose in taper hole 3 A 3 Require repair or replacement. See note (10) below.

Taper hole elongated 3 A 3 Require replacement. See note (11)

Threads damaged 3 A 3 Require repair or replacement.

Threads stripped (threads missing) 3 A 3 Require replacement. See note (10)

NOTE: (1) If greaseable, grease joint. If problem persists or joint is non-greaseable, require replacement.

(2) Cracked grease boot will allow contaminants to enter joint and will accelerate wear.

(3) Lack of grease boot will allow contaminants to enter joint and will accelerate wear.

(4) Torn grease boot will allow contaminants to enter joint and will accelerate wear.

(5) Lack of grease seal will allow contaminants to enter joint and will accelerate wear.

(6) Torn grease seal will allow contaminants to enter joint and will accelerate wear.

(7) If manufacturer's procedures for inspection exist, use those procedures; otherwise, use an approved inspection method such as the dry park check.

(8) Excessive looseness is defined as being significant enough

*** SUSPENSION UNIFORM INSPECTION GUIDELINES ***

Article Text (p. 28)

1987 Volkswagen Quantum/Quantum Syncro

For Volkswagen Technical Site

Copyright © 1998 Mitchell Repair Information Company, LLC

Sunday, March 19, 2000 12:41AM

to affect vehicle handling or structural integrity.

(9) Check for bent stud of damaged taper hole.

(10) Check for damaged taper hole.

(11) Check for damaged stud.

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

POWER STEERING HOSES

POWER STEERING HOSES

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Condition	3	Code	3	Procedure
-----------	---	------	---	-----------

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Blistered	3	B	3	Require replacement.
-----------	---	---	---	----------------------

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Blocked	3	A	3	Require repair or replacement.
---------	---	---	---	--------------------------------

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Fitting threads damaged	3	A	3	Require repair or replacement.
-------------------------	---	---	---	--------------------------------

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Fitting threads stripped	3	A	3	Require replacement.
--------------------------	---	---	---	----------------------

(threads missing) 3 3

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Inner fabric (webbing) cut	3	A	3	Require replacement.
----------------------------	---	---	---	----------------------

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Leaking	3	A	3	Require repair or replacement.
---------	---	---	---	--------------------------------

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Missing	3	C	3	Require replacement.
---------	---	---	---	----------------------

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Outer covering is cracked	3	B	3	Require replacement.
---------------------------	---	---	---	----------------------

to the extent that the 3 3

inner fabric of hose is 3 3

visible 3 3

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Restricted	3	A	3	Require repair or replacement.
------------	---	---	---	--------------------------------

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

POWER STEERING (HYDRAULIC) PUMPS

If diagnosis has determined that complete disassembly is necessary to determine the extent of the system failure, the suggestion may be made to rebuild or replace the power steering pump. Repair or replacement of the following components may be required if performed as part of a power steering pump overhaul or rebuild service to meet a minimum rebuild standard.

POWER STEERING (HYDRAULIC) PUMPS

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Condition	3	Code	3	Procedure
-----------	---	------	---	-----------

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Attaching hardware bent	3	B	3	Require repair or replacement of
-------------------------	---	---	---	----------------------------------

3 3 bent part.

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Attaching hardware broken	3	A	3	Require replacement of broken
---------------------------	---	---	---	-------------------------------

*** SUSPENSION UNIFORM INSPECTION GUIDELINES ***

Article Text (p. 29)

1987 Volkswagen Quantum/Quantum Syncro

For Volkswagen Technical Site

Copyright © 1998 Mitchell Repair Information Company, LLC

Sunday, March 19, 2000 12:41AM

```

3      3 part.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
Attaching hardware loose 3 A 3 Require repair or replacement of
3      3 loose part.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
Attaching hardware missing 3 C 3 Require replacement of missing
3      3 part.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
Attaching hardware threads 3 A 3 Require repair or replacement of
damaged 3      3 part with damaged threads.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
Attaching hardware threads 3 A 3 Require replacement of part with
stripped (threads missing) 3      3 stripped threads.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
Belt alignment incorrect 3 B 3 Further inspection required.
3      3 See note (1) below.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
Belt cracked 3 A,1 3 Suggest replacement.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
Belt frayed 3 A,1 3 Suggest replacement.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
Belt missing 3 C 3 Require replacement.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
Belt noisy 3 B,2 3 Further inspection required.
3      3 See note (2) below.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
Belt plies separated 3 A 3 Require replacement.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
Belt tension out of spec 3 B 3 Require adjustment or replacement.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
Belt worn beyond adjustment 3 B 3 Require replacement.
range 3      3
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
Belt worn so it contacts 3 A 3 Require replacement.
bottom of pulley 3      3
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
Binding 3 A 3 Require repair or replacement.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
Fluid at or beyond service 3 C,3 3 Suggest fluid change.
interval 3      3
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
Fluid contaminated 3 B 3 Require flushing and refilling of
3      3 the system. See note (3) below.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
Fluid level incorrect 3 B 3 Require adjustment of fluid level.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
Inadequate assist 3 A 3 Further inspection required.
3      3 See note (4) below.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
Leaking 3 A 3 Require repair or replacement.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
Noise 3 B,2 3 Further inspection required.
```

*** SUSPENSION UNIFORM INSPECTION GUIDELINES ***

Article Text (p. 30)

1987 Volkswagen Quantum/Quantum Syncro

For Volkswagen Technical Site

Copyright © 1998 Mitchell Repair Information Company, LLC

Sunday, March 19, 2000 12:41AM

3 3 See note (5) below.

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Pulley bent 3 A 3 Require repair or replacement of
3 3 pulley.

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Pulley missing 3 C? 3 Require replacement of pulley.

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Remote reservoir leaking 3 A 3 Require replacement of reservoir.

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Reservoir cap broken 3 A 3 Require replacement of cap.

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Reservoir cap missing 3 C 3 Require replacement of cap.

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Seized 3 A 3 Require replacement.

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Threads damaged 3 A 3 Require repair or replacement.

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Threads stripped (threads 3 A 3 Require replacement.
missing) 3 3

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

NOTE: (1) Determine cause of incorrect alignment and require repair.

(2) Determine cause of noise and suggest repair.

(3) Determine and correct source of contamination. OEM
specifications must be followed for fluid type.

(4) If pump is source of inadequate assist, require repair or
replacement.

(5) If noise is isolated to pump, suggest repair or replacement.

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

RADIUS ARMS

RADIUS ARMS

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Condition 3 Code 3 Procedure

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Attaching hardware broken 3 A 3 Require replacement of broken
3 3 part.

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Attaching hardware 3 A 3 Require replacement of incorrect
incorrect 3 3 part.

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Attaching hardware loose 3 A 3 Require repair or replacement of
3 3 loose part.

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Attaching hardware missing 3 C 3 Require replacement of missing
3 3 part.

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Attaching hardware threads 3 A 3 Require repair or replacement of
damaged 3 3 part with damaged threads.

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Attaching hardware threads 3 A 3 Require replacement of part with
stripped (threads missing) 3 3 stripped threads.

(6) Torn grease seal will allow contaminants to enter joint and

[illegible]

*** SUSPENSION UNIFORM INSPECTION GUIDELINES ***

Article Text (p. 34)

1987 Volkswagen Quantum/Quantum Syncro

For Volkswagen Technical Site

Copyright © 1998 Mitchell Repair Information Company, LLC

Sunday, March 19, 2000 12:41AM

Attaching hardware corroded	3	A	3	Require replacement of corroded
affecting structural	3		3	part, if available; otherwise,
integrity	3		3	replace shock or strut.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA				
Attaching hardware	3	A	3	Require replacement of incorrect
incorrect	3		3	part, if available; otherwise,
	3		3	replace shock or strut.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA				
Attaching hardware loose	3	A	3	Require repair or replacement of
	3		3	loose part, if available;
	3		3	otherwise, replace shock or strut.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA				
Attaching hardware missing	3	C	3	Require replacement of missing
	3		3	part, if available; otherwise,
	3		3	replace shock or strut.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA				
Attaching hardware threads	3	A	3	Require repair or replacement of
damaged	3		3	part with damaged threads, if
	3		3	available; otherwise, replace
	3		3	shock or strut.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA				
Attaching hardware threads	3	A	3	Require replacement of part with
stripped (threads missing)	3		3	stripped threads, if available;
	3		3	otherwise, replace shock or strut.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA				
Binding	3	A	3	Require replacement.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA				
Body dented	3	A	3	Further inspection required.
	3		3	See note (1) below.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA				
Body punctured	3	A	3	Require replacement.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA				
Brake hose bracket bent	3	B	3	Require repair or replacement.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA				
Brake hose bracket missing	3	C	3	Require replacement.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA				
Brake hose bracket threads	3	C	3	Require repair or replacement.
damaged	3		3	
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA				
Brake hose bracket threads	3	C	3	Require replacement.
stripped (threads missing)	3		3	
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA				
Compression bumper missing	3	C	3	Require replacement of compression
	3		3	bumper.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA				
Compression bumper split	3	A,1	3	Suggest replacement of compression
	3		3	bumper.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA				
Damping (none)	3	A	3	Require replacement.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA				
Dust boot (bellows) split	3	B,2	3	Suggest replacement of boot.
	3		3	See note (2) below.

*** SUSPENSION UNIFORM INSPECTION GUIDELINES ***

Article Text (p. 35)

1987 Volkswagen Quantum/Quantum Syncro

For Volkswagen Technical Site

Copyright © 1998 Mitchell Repair Information Company, LLC

Sunday, March 19, 2000 12:41AM

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Dust boot (bellows) missing³ B,2³ Suggest replacement of boot.

³ See (3) note below.

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Dust boot (bellows) torn³ B,2³ Suggest replacement of boot.

³ See note (4) below.

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Dust shield broken³ B,2³ Suggest replacement. See note (4).

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Dust shield missing³ B,2³ Suggest replacement. See note (4).

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Gland nut (strut housing³ A³ Require replacement of nut and/or
cap) is not removable³
using appropriate tool³³ housing. See note (5) below.

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Gland nut (strut housing³ A³ Require repair or replacement of
cap) threads damaged³³ nut.

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Gland nut (strut housing³ A³ Require replacement of nut.

cap) threads stripped³
(threads missing)³³

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Housing dented³ A³ Further inspection required.

³ See note (6) below.

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Housing punctured³ A³ Require replacement.

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Jounce bumper missing³ C³ Require replacement of jounce
bumper.³

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Jounce bumper split³ 1?³ Suggest replacement of jounce
bumper.³

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Leaking oil, enough for³ A³ Require replacement. See caution
fluid to be running down³
the body³³ below.

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

CAUTION: If the strut cartridge has been replaced previously, the oil
on the strut housing may be filler oil. The technician must
identify the source of the oil.

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Noise³ B,2³ Further inspection required.

³ See note (7) below.

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Piston rod bent³ A³ Require replacement.

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Piston rod broken³ A³ Require replacement.

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Piston rod has surface³ B,2³ Suggest replacement.
defect³³

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Piston rod threads damaged³ A³ Require repair or replacement.

*** SUSPENSION UNIFORM INSPECTION GUIDELINES ***

Article Text (p. 36)

1987 Volkswagen Quantum/Quantum Syncro

For Volkswagen Technical Site

Copyright © 1998 Mitchell Repair Information Company, LLC

Sunday, March 19, 2000 12:41AM

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Piston rod threads stripped³ A ³ Require replacement.

(threads missing) ³ ³

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Seized ³ A ³ Require replacement.

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Shock missing ³ C ³ Require replacement.

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Strut housing bent ³ A ³ Require replacement.

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Strut housing cap (gland ³ A ³ Require replacement of nut and/or
nut) is not removable ³ ³ housing. See note (5) below.
using appropriate tool ³ ³

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Strut housing cap (gland ³ A ³ Require repair or replacement of
nut) threads damaged ³ ³ nut.

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Strut housing cap (gland ³ A ³ Require replacement of nut.
nut) threads stripped ³ ³
(threads missing) ³ ³

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Strut housing severely ³ A ³ Require replacement.
corroded, affecting ³ ³
structural integrity ³ ³

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Strut housing threads ³ A ³ Require repair or replacement.
damaged ³ ³

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Strut housing threads ³ A ³ Require replacement.
stripped (threads missing)³ ³

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Tire cupping ³ A ³ Further inspection required.
³ ³ See note (8) below

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

NOTE: (1) Require replacement of units where dents restrict shock or
strut piston rod movement. If dents don't restrict movement,
no service is suggested or required. Especially critical on
mono-tube shocks.

(2) This condition can lead to damage of the piston rod, which,
in turn, causes premature piston rod seal wear.

(3) This condition can lead to damage of the piston rod, which
causes piston rod seal wear.

(4) This condition can lead to damage of the piston rod, which,
in turn, causes premature piston rod seal wear.

(5) Only required if replacing cartridge.

(6) Require replacement of units where dents restrict shock or
strut piston rod movement. If dents don't restrict movement,
no service is suggested or required. Especially critical on
mono-tube shocks.

(7) If noise is isolated to shock or strut, suggest replacement.

(8) Although shocks or struts may have contributed to tire
cupping, an inspection is needed of the entire suspension

[illegible]

*** SUSPENSION UNIFORM INSPECTION GUIDELINES ***

Article Text (p. 38)

1987 Volkswagen Quantum/Quantum Syncro

For Volkswagen Technical Site

Copyright © 1998 Mitchell Repair Information Company, LLC

Sunday, March 19, 2000 12:41AM

Condition	3	Code	3	Procedure
Attaching hardware bent	3	B	3	Require repair or replacement of bent part.
Attaching hardware broken	3	A	3	Require replacement of broken part.
Attaching hardware corroded affecting structural integrity	3	A	3	Require replacement of corroded part.
Attaching hardware incorrect	3	A	3	Require replacement of incorrect part.
Attaching hardware loose	3	A	3	Require repair or replacement of loose part.
Attaching hardware missing	3	C	3	Require replacement of missing part.
Attaching hardware threads damaged	3	A	3	Require repair or replacement of part with damaged threads.
Attaching hardware threads stripped (threads missing)	3	A	3	Require replacement of part with stripped threads.
Broken (all springs except secondary leave(s) on multi-leaf springs)	3	A	3	Require replacement.
Coil clash	3		3	Require ride height check. See note (1) below.
Coil spring insulator deteriorated	3	B,2	3	Suggest replacement of insulator.
Coil spring insulator missing	3	B,2	3	Suggest replacement of insulator.
Coil spring insulator split	3	B,2	3	Suggest replacement of insulator.
Coil spring plastic coating deteriorated - rust present	3	A	3	Refer to manufacturer's service requirements. See note (2) below.
Composite spring damaged	3	A	3	Further inspection required. See note (3) below.
Cracked (all springs except composite leaf and secondary leave(s) on	3	A	3	Require replacement.

Sunday, March 19, 2000 12:41AM

Condition	Code	Procedure
Attaching hardware bent	B	Require repair or replacement of bent part.

*** SUSPENSION UNIFORM INSPECTION GUIDELINES ***

Article Text (p. 40)

1987 Volkswagen Quantum/Quantum Syncro

For Volkswagen Technical Site

Copyright © 1998 Mitchell Repair Information Company, LLC

Sunday, March 19, 2000 12:41AM

Attaching hardware broken	3	A	3	Require replacement of broken
	3		3	part.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA				
Attaching hardware loose	3	A	3	Require repair or replacement of
	3		3	loose part.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA				
Attaching hardware missing	3	C	3	Require replacement of missing
	3		3	part.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA				
Attaching hardware threads	3	A	3	Require repair or replacement of
damaged	3		3	part with damaged threads.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA				
Attaching hardware threads	3	A	3	Require replacement of part with
stripped (threads missing)	3		3	stripped threads.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA				
Blocked	3	A	3	Require repair or replacement.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA				
Fitting incorrect (such as	3	B	3	Require replacement.
compression fitting)	3		3	
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA				
Flare type incorrect	3	B	3	Required replacement.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA				
Leaking	3	A	3	Require tightening or replacement.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA				
Line type incorrect	3	B	3	Require replacement.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA				
Restricted	3	A	3	Require replacement.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA				
Routed incorrectly	3	B	3	Require routing correction.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA				
Rust-pitted	3	A,1	3	Suggest replacement.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA				
Rust pitted affecting	3	A	3	Require replacement.
structural integrity	3		3	
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA				

STEERING ARMS

STEERING ARMS

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA				
Condition	3	Code	3	Procedure
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA				
Attaching hardware bent	3	B	3	Require repair or replacement of
	3		3	bent part.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA				
Attaching hardware broken	3	A	3	Require replacement of broken
	3		3	part.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA				
Attaching hardware	3	A	3	Require replacement of incorrect
incorrect	3		3	part.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA				
Attaching hardware loose	3	A	3	Require repair or replacement of

*** SUSPENSION UNIFORM INSPECTION GUIDELINES ***

Article Text (p. 41)

1987 Volkswagen Quantum/Quantum Syncro

For Volkswagen Technical Site

Copyright © 1998 Mitchell Repair Information Company, LLC

Sunday, March 19, 2000 12:41AM

3 3 loose part.

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Attaching hardware missing 3 C 3 Require replacement of missing
3 3 part.

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Attaching hardware threads 3 A 3 Require repair or replacement of
damaged 3 3 part with damaged threads.

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Attaching hardware threads 3 A 3 Require replacement of part with
stripped (threads missing) 3 3 stripped threads.

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Bent 3 B 3 Require replacement.

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Broken 3 A 3 Require replacement.

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Taper hole elongated 3 A 3 Require replacement. See note (1).

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Threads damaged 3 A 3 Require repair or replacement.

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Threads stripped (threads 3 A 3 Require replacement.
missing) 3 3

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

NOTE: (1) Check for damaged stud.

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

STEERING DAMPERS

The following procedures are only required if the vehicle was originally equipped from the factory with a steering damper. If the steering damper is an add-on unit, then the unit may be removed instead of repairing or replacing.

STEERING DAMPERS

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Condition 3 Code 3 Procedure

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Attaching hardware bent 3 B 3 Require repair or replacement of
3 3 bent part, if available;
3 3 otherwise, replace steering
3 3 damper.

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Attaching hardware broken 3 A 3 Require replacement of broken
3 3 part, if available; otherwise,
3 3 replace steering damper.

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Attaching hardware corroded 3 A 3 Require replacement of corroded
affecting structural 3 3 part, if available; otherwise,
integrity 3 3 replace steering damper.

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Attaching hardware 3 A 3 Require replacement of incorrect
incorrect 3 3 part, if available; otherwise,
3 3 replace steering damper.

Sunday, March 19, 2000 12:41AM

[illegible]

Condition	Code	Procedure
Attaching hardware broken	A	Require replacement of broken part.
Attaching hardware loose	A	Require repair or replacement of loose part.
Attaching hardware missing	C	Require replacement of missing part.
Attaching hardware threads damaged	A	Require repair or replacement of part with damaged threads.
Attaching hardware threads stripped (threads missing)	A	Require replacement of part with stripped threads.
Binding	A	Require repair or replacement
Flex coupler binding	A	Require repair or replacement of

	3	3	coupler.
Flex coupler loose	3	A	3 Require repair or replacement of
	3		3 coupler.
Flex coupler missing parts	3	A	3 Require repair or replacement of
	3		3 coupler.
Flex coupler soft/spongy	3	A	3 Require replacement of coupler.
Flex coupler torn	3	A	3 Require replacement of coupler.
Fluid contaminated	3	B	3 Require flushing and refilling
	3		3 of the system. See note (1) below.
Gasket leaking	3	A	3 Require repair or replacement of
	3		3 gasket.
Housing leaking	3	A	3 Require replacement.
Hydraulic fittings leaking	3	A	3 Require repair or replacement of
	3		3 fittings.
Inadequate power assist	3	A	3 Further inspection required.
	3		3 See note (2) below.
Lash exceeds manufacturer's specifications	3	B	3 Require repair or replacement.
	3		3
Seal leaking	3	A	3 Require repair or replacement of
	3		3 seal and/or mating part.
Splines damaged	3	A	3 Require repair or replacement of
	3		3 splines.
Splines stripped	3	A	3 Require replacement of splines.
Steering coupler shield cracked	3	B,2	3 Suggest replacement.
	3		3
Steering coupler shield missing	3	C	3 Require replacement.
	3		3
Threads damaged	3	A	3 Require repair or replacement of
	3		3 part with damaged threads.
Threads stripped (threads missing)	3	A	3 Require replacement of part with
	3		3 stripped threads.
U-joint binding	3	A	3 Require repair or replacement of
	3		3 joint.

bellows boot cracked (not
through) 3 3 suggest replacement of bellows
boot.

* SUSPENSION UNIFORM INSPECTION GUIDELINES *

Article Text (p. 46)

1987 Volkswagen Quantum/Quantum Syncro

For Volkswagen Technical Site

Copyright © 1998 Mitchell Repair Information Company, LLC

Sunday, March 19, 2000 12:41AM

[illegible]

Bellows boot missing	3	C	3	Require replacement of bellows
	3		3	boot.

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Bellows boot not sealing	3	A	3	Require repair or replacement of
	3		3	bellows boot.

.....

```

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
Bellows boot torn          3  A      3  Require replacement of bellows
                             3          3  boot.

```

```

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
Bellows boot twisted (from 3 B 3 Require repair.
toe adjustment) 3 3

```

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Fitting leaking 3 A 3 Require repair or replacement.

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Fitting missing ³ A ³ Require replacement of fitting.

```

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
Fitting threads damaged      3  A      3  Require repair or replacement of
                               3          3  part with damaged threads.
.....

```

```

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
Fitting threads stripped      3  A      3  Require replacement of part with
(threads missing)            3          3  stripped threads.

```

Flex coupler binding	3	A	3	Require repair or replacement of
	3		3	coupler.

Flex coupler loose	3	A	3	Require repair or replacement of
	3		3	coupler.

Flex coupler missing parts 3 A 3 Require repair or replacement of
3 3 coupler.

Flex coupler soft/spongy 3 A 3 Require replacement of coupler.

Flex coupler torn ³ A ³ Require replacement of coupler.

Fluid contaminated				3	B	3	Require flushing and refilling of
				3		3	the system. See note (1) below.

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Gasket leaking 3 A 3 Require repair or replacement.

Hard steering on cold	3	A,1	3 Suggest repair or replacement.
start-up	3		3 See note (2) below.

Housing cracked, affecting structural integrity 3 B 3 Require replacement.

Housing leaking ³ A ³ Require replacement.

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA				
Inadequate power assist	3	A	3	Further inspection required.
	3		3	See note (3) below.

[illegible]

*** SUSPENSION UNIFORM INSPECTION GUIDELINES ***

Article Text (p. 47)

1987 Volkswagen Quantum/Quantum Syncro

For Volkswagen Technical Site

Copyright © 1998 Mitchell Repair Information Company, LLC

Sunday, March 19, 2000 12:41AM

Lash exceeds manufacturer's³ B ³ Require repair or replacement.
specifications ³ ³
AAAAAA
Seal leaking ³ A ³ Require repair or replacement.
AAAAAA
Splines damaged ³ A ³ Require repair or replacement.
AAAAAA
Splines stripped (splines ³ A ³ Require replacement.
missing) ³ ³
AAAAAA
Steel line blocked ³ A ³ Require repair or replacement of
AAAAAA line.
Steel line leaking ³ A ³
AAAAAA
Steel line missing ³ C ³ Require replacement of line.
AAAAAA
Steel line restricted ³ A ³ Require repair or replacement of
³ ³ line.
AAAAAA
Steering coupler shield ³ B,2 ³ Suggest replacement.
cracked ³ ³
AAAAAA
Steering coupler shield ³ C ³ Require replacement.
missing ³ ³
AAAAAA
Steering coupler shield ³ B,2 ³ Suggest replacement.
torn ³ ³
AAAAAA
Threads damaged ³ A ³ Require repair or replacement of
³ ³ part with damaged threads.
AAAAAA
Threads stripped (threads ³ A ³ Require replacement of part with
missing) ³ ³ stripped threads.
AAAAAA
U-joint binding ³ A ³ Require repair or replacement of
³ ³ joint.
AAAAAA
U-joint loose ³ A ³ Require repair or replacement of
³ ³ joint.
AAAAAA
Unequal power assist ³ A ³ Require repair or replacement.
AAAAAA
NOTE: (1) Determine and correct source of contamination.
Follow OE specifications for fluid type.
(2) Indicates internal wear.
(3) If steering gear is source of inadequate assist, require
repair or replacement.
AAAAAA

STEERING KNUCKLES

STEERING KNUCKLES

*** SUSPENSION UNIFORM INSPECTION GUIDELINES ***

Article Text (p. 48)

1987 Volkswagen Quantum/Quantum Syncro

For Volkswagen Technical Site

Copyright © 1998 Mitchell Repair Information Company, LLC

Sunday, March 19, 2000 12:41AM

Condition			3	Code	3	Procedure
Attaching hardware bent						
	3	B	3	Require repair or replacement of bent part.		
Attaching hardware broken						
	3	A	3	Require replacement of broken part.		
Attaching hardware incorrect						
	3	A	3	Require replacement of incorrect part.		
Attaching hardware loose						
	3	A	3	Require repair or replacement of loose part.		
Attaching hardware missing						
	3	C	3	Require replacement of missing part.		
Attaching hardware threads damaged						
	3	A	3	Require repair or replacement of part with damaged threads.		
Attaching hardware threads stripped (threads missing)						
	3	A	3	Require replacement of part with stripped threads.		
Bent						
	3	B	3	Require replacement.		
Broken						
	3	A	3	Require replacement.		
Pinch bolt incorrect						
	3	B	3	Require replacement with bolt that meets OE design.		
Pinch bolt loose						
	3	B	3	Require repair.		
Pinch bolt missing						
	3	B	3	Require replacement.		
Pinch bolt tabs deformed (pinched together), .032" or more before clamping						
	3	B	3	Require replacement.		
	3		3	See note (1) below.		
Taper hole elongated						
	3	A	3	Require replacement. See note (2).		
Threads damaged						
	3	A	3	Require repair or replacement.		
Threads stripped (threads missing)						
	3	A	3	Require repair or replacement.		
NOTE: (1) Steering knuckle deformation can cause pinch bolt breakage.						
(2) Check for damaged stud.						

STRIKE OUT BUMPERS

*** SUSPENSION UNIFORM INSPECTION GUIDELINES ***

Article Text (p. 49)

1987 Volkswagen Quantum/Quantum Syncro

For Volkswagen Technical Site

Copyright © 1998 Mitchell Repair Information Company, LLC

Sunday, March 19, 2000 12:41AM

STRIKE OUT BUMPERS

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA			
Condition	3	Code	3 Procedure
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA			
Attaching hardware broken	3	A	3 Require replacement of broken
	3		3 part.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA			
Attaching hardware corroded	3	A	3 Require replacement of corroded
affecting structural	3		3 part.
integrity	3		3
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA			
Attaching hardware loose	3	A	3 Require repair or replacement of
	3		3 loose part.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA			
Attaching hardware missing	3	C	3 Require replacement of missing
	3		3 part.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA			
Attaching hardware threads	3	A	3 Require repair or replacement of
damaged	3		3 part with damaged threads.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA			
Attaching hardware threads	3	A	3 Require replacement of part with
stripped (threads missing)	3		3 stripped threads.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA			
Missing	3	C	3 Require replacement.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA			
Split	3	A,1	3 Suggest replacement.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA			

STRUT RODS

STRUT RODS

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA			
Condition	3	Code	3 Procedure
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA			
Adjusting nut seized	3	A	3 Require repair or replacement.
	3		3 See note (1) below.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA			
Attaching hardware bent	3	B	3 Require repair or replacement of
	3		3 bent part, if available;
	3		3 otherwise, replace strut rod.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA			
Attaching hardware broken	3	A	3 Require replacement of broken
	3		3 part, if available; otherwise,
	3		3 replace strut rod.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA			
Attaching hardware	3	A	3 Require replacement of incorrect
incorrect	3		3 part, if available; otherwise,
	3		3 replace strut rod.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA			
Attaching hardware loose	3	A	3 Require repair or replacement of
	3		3 loose part, if available;
	3		3 otherwise, replace strut rod.

*** SUSPENSION UNIFORM INSPECTION GUIDELINES ***

Article Text (p. 50)

1987 Volkswagen Quantum/Quantum Syncro

For Volkswagen Technical Site

Copyright © 1998 Mitchell Repair Information Company, LLC

Sunday, March 19, 2000 12:41AM

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Attaching hardware missing	3	C	3	Require replacement of missing
	3		3	part, if available; otherwise,
	3		3	replace strut rod.

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Attaching hardware threads	3	A	3	Require repair or replacement of
damaged	3		3	part with damaged threads, if
	3		3	available; otherwise, replace
	3		3	strut rod.

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Attaching hardware threads	3	A	3	Require replacement of part with
stripped (threads missing)	3		3	stripped threads, if available;
	3		3	otherwise, replace strut rod.

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Attaching (mating) hole	3	A	3	Require repair or replacement of
oversized	3		3	frame.

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Attaching point on frame	3	A	3	Require repair of frame.
corroded, affecting	3		3	
structural integrity	3		3	

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Bent	3	A	3	Require replacement.
------	---	---	---	----------------------

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Mating (attaching) hole	3	A	3	Require repair or replacement of
oversized	3		3	frame.

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Threads damaged	3	A	3	Require repair or replacement.
-----------------	---	---	---	--------------------------------

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Threads stripped (threads	3	A	3	Require replacement.
missing)	3		3	

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

NOTE: (1) Only required if an alignment is being performed.

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

STRUT UPPER BEARING PLATE ASSEMBLIES

NOTE: When the following guidelines indicate replacement of bearing, only the bearing should be replaced if it is available separately; otherwise, replace the bearing plate assembly.

STRUT UPPER BEARING PLATE ASSEMBLIES

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Condition	3	Code	3	Procedure
-----------	---	------	---	-----------

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Attaching hardware broken	3	A	3	Require replacement of broken
	3		3	part, if available; otherwise,
	3		3	replace bearing plate assembly.

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Attaching hardware loose	3	A	3	Require repair or replacement of
	3		3	loose part, if available;
	3		3	otherwise, replace bearing plate

*** SUSPENSION UNIFORM INSPECTION GUIDELINES ***

Article Text (p. 51)

1987 Volkswagen Quantum/Quantum Syncro

For Volkswagen Technical Site

Copyright © 1998 Mitchell Repair Information Company, LLC

Sunday, March 19, 2000 12:41AM

	3	3	assembly.
Attaching hardware missing	3 C	3	Require replacement of missing
	3	3	part, if available; otherwise,
	3	3	replace bearing plate assembly.
Attaching hardware threads	3 A	3	Require repair or replacement of
damaged	3	3	part with damaged threads, if
	3	3	available; otherwise, replace
	3	3	bearing plate assembly.
Attaching hardware threads	3 A	3	Require replacement of part with
stripped (threads missing)	3	3	stripped threads, if available;
	3	3	otherwise, replace bearing plate
	3	3	assembly.
Bearing axial or radial	3 B	3	Require replacement of bearing.
movement exceeds vehicle	3	3	
manufacturer's specs	3	3	
Bearing binding	3 A	3	Require replacement of bearing.
Bearing missing	3 C	3	Require replacement of bearing.
Bearing seized	3 A	3	Require replacement of bearing.
Bent	3 B	3	Require replacement.
Holes distorted	3 A	3	Require replacement.
Missing	3 C	3	Require replacement.
Severely corroded,	3 A	3	Require replacement.
affecting structural	3	3	
integrity	3	3	

SWAY BAR LINKS

SWAY BAR LINKS			
Condition	3 Code	3	Procedure
Attaching hardware	3 A	3	Require replacement of incorrect
incorrect	3	3	part, if available; otherwise,
	3	3	replace link.
Attaching hardware loose	3 A	3	Require repair or replacement of
	3	3	loose part, if available;
	3	3	otherwise, replace link.
Attaching hardware missing	3 C	3	Require replacement of missing

NOTE: (1) If manufacturer's procedures for inspection exist, use those procedures; otherwise, use an approved inspection method such as the dry park check.

* SUSPENSION UNIFORM INSPECTION GUIDELINES *

Article Text (p. 53)

1987 Volkswagen Quantum/Quantum Syncro

For Volkswagen Technical Site

Copyright © 1998 Mitchell Repair Information Company, LLC

Sunday, March 19, 2000 12:41AM

- (2) Excessive looseness is defined as being significant enough to affect vehicle handling or structural integrity.
- (3) Cracked grease boot will allow contaminants to enter the joint and will accelerate wear.
- (4) Lack of grease boot will allow contaminants to enter the joint and will accelerate wear.
- (5) Torn grease boot will allow contaminants to enter the joint and will accelerate wear.
- (6) Check for bent stud or damaged taper hole.
- (7) Check for damaged taper hole.

[illegible]

SWAY BARS

SWAY BARS

[illegible]

Condition	3 Code 3	Procedure
-----------	----------	-----------

[illegible]

Attaching hardware broken	3	A	3	Require replacement of broken
	3		3	part, if available; otherwise,
	3		3	replace sway bar.

[illegible]

Attaching hardware corroded ³	A	³ Require replacement of corroded
affecting structural	³	³ part, if available; otherwise,
integrity	³	³ replace sway bar.

[illegible]

Attaching hardware loose	3	A	3	Require repair or replacement of
	3		3	loose part, if available;
	3		3	otherwise, replace sway bar.

[illegible]

Attaching hardware missing	3	C	3	Require replacement of missing
	3		3	part, if available; otherwise,
	3		3	replace sway bar.

[illegible]

Attaching hardware threads	3	A	3	Require repair or replacement of
damaged	3		3	part with damaged threads, if
	3		3	available; otherwise, replace sway
	3		3	bar.

[illegible]

Attaching hardware threads	3	A	3	Require replacement of part with
stripped (threads missing)	3		3	stripped threads, if available;
	3		3	otherwise, replace sway bar.

[illegible]

Bent B Require replacement.

[illegible]

Broken ³ A ³ Require replacement.

ELEMENT

Threads damaged 3 A 3 Require repair or replacement.

The cables damaged in the repair or replacement:

 11 cables damaged

```
Threads stripped (threads 3 A 3 Require replacement.
missing) 3 3
```

[illegible]

*** SUSPENSION UNIFORM INSPECTION GUIDELINES ***

Article Text (p. 54)

1987 Volkswagen Quantum/Quantum Syncro

For Volkswagen Technical Site

Copyright © 1998 Mitchell Repair Information Company, LLC

Sunday, March 19, 2000 12:41AM

TIE ROD ENDS (INNER & OUTER)

TIE ROD ENDS (INNER & OUTER)

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA			
Condition	3	Code	3 Procedure
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA			
Attaching hardware incorrect	3	A	3 Require replacement of incorrect part, if available; otherwise, replace tie rod end.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA			
Attaching hardware loose	3	A	3 Require repair or replacement of loose part, if available; otherwise, replace tie rod end.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA			
Attaching hardware missing	3	C	3 Require replacement of missing part, if available; otherwise, replace tie rod end.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA			
Attaching hardware threads damaged	3	A	3 Require repair or replacement of part with damaged threads, if available; otherwise, replace tie rod end.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA			
Attaching hardware threads stripped (threads missing)	3	A	3 Require replacement of part with stripped threads, if available; otherwise, replace tie rod end.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA			
Adjusting sleeve bent	3	B	3 Require replacement of sleeve or tie rod end.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA			
Adjusting sleeve clamps out of position	3	B	3 Require repair.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA			
Adjusting sleeve corroded, affecting structural integrity	3	A	3 Require replacement of sleeve or tie rod end.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA			
Adjusting sleeve missing	3	C	3 Require replacement of sleeve or tie rod end.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA			
Adjusting sleeve seized	3	A	3 Require repair or replacement. See note (1) below.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA			
Adjusting sleeve threads damaged	3	A	3 Require repair or replacement of sleeve or tie rod end.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA			
Adjusting sleeve threads stripped (threads missing)	3	A	3 Require replacement of sleeve or tie rod end.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA			
Binding	3	A	3 Further inspection required. See note (2) below.

*** SUSPENSION UNIFORM INSPECTION GUIDELINES ***

Article Text (p. 55)

1987 Volkswagen Quantum/Quantum Syncro

For Volkswagen Technical Site

Copyright © 1998 Mitchell Repair Information Company, LLC

Sunday, March 19, 2000 12:41AM

Grease boot cracked 3 3 Suggest replacement. See note (3).

Grease boot missing 3 3 Suggest replacement. See note (4).

Grease boot torn 3 3 Suggest replacement. See note (5).

Grease fitting broken 3 A 3 Require replacement of grease fitting.

Grease fitting missing 3 C 3 Require replacement of grease fitting.

Grease fitting won't seal 3 A 3 Require replacement of grease fitting.

Grease seal missing 3 B,2 3 Suggest replacement of seal. See note (4) below.

Grease seal torn 3 B,2 3 Suggest replacement of seal. See note (5) below.

Greaseable tie rod end 3 B,2 3 Suggest replacement of grease will not take grease 3 fitting. See note (6) below.

Looseness (perceptible 3 A,1 3 Suggest replacement. See note (7). horizontal movement) 3

CAUTION: DO NOT use pliers or pry bar to check ball and socket movement. Use only moderate hand pressure.

Looseness exceeds 3 B 3 Require replacement. manufacturer's specs 3

Looseness that is excessive 3 B 3 Require replacement. See notes (7) and (8), caution.

Nut on stud loose 3 A 3 Require repair or replacement of nut. See note (9) below.

Seized 3 A 3 Require replacement

Stud bent 3 B 3 Require replacement. See note (10)

Stud broken 3 A 3 Require replacement. See note (10)

Threads damaged 3 A 3 Require repair or replacement.

Threads stripped (threads 3 A 3 Require replacement. See note (10) missing) 3

NOTE: (1) Only required if toe needs to be adjusted.

*** SUSPENSION UNIFORM INSPECTION GUIDELINES ***

Article Text (p. 56)

1987 Volkswagen Quantum/Quantum Syncro

For Volkswagen Technical Site

Copyright © 1998 Mitchell Repair Information Company, LLC

Sunday, March 19, 2000 12:41AM

- (2) If greaseable, grease joint. If problem persists or joint is non-greaseable, require replacement.
- (3) Cracked grease boot will allow contaminants to enter joint and will accelerate wear.
- (4) Lack of grease boot will allow contaminants to enter joint and will accelerate wear.
- (5) Torn grease boot will allow contaminants to enter joint and will accelerate wear.
- (6) If greaseable tie rod end will not take grease after replacing the grease fitting, suggest replacement of tie rod end.
- (7) If manufacturer's procedures for inspection exist, use those procedures; otherwise, use an approved inspection method such as the dry park check.
- (8) Excessive looseness is defined as being significant enough to affect vehicle handling or structural integrity.
- (9) Check for bent stud or damaged taper hole.
- (10) Check for damaged taper hole.

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

TRACK BARS

TRACK BARS

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

Condition	3	Code	3	Procedure
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA				
Attaching hardware incorrect	3	A	3	Require replacement of incorrect part, if available; otherwise, replace track bar.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA				
Attaching hardware loose	3	A	3	Require repair or replacement of loose part, if available; otherwise, replace track bar.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA				
Attaching hardware missing	3	C	3	Require replacement of missing part, if available; otherwise, replace track bar.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA				
Attaching hardware threads damaged	3	A	3	Require repair or replacement of part with damaged threads, if available; otherwise, replace track bar.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA				
Attaching hardware threads stripped (threads missing)	3	A	3	Require replacement of part with stripped threads, if available; otherwise, replace track bar.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA				
Bent	3	B	3	Require replacement.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA				
Corroded, affecting structural integrity	3	A	3	Require replacement.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA				

TRAILING ARMS

*** SUSPENSION UNIFORM INSPECTION GUIDELINES ***

Article Text (p. 58)

1987 Volkswagen Quantum/Quantum Syncro

For Volkswagen Technical Site

Copyright © 1998 Mitchell Repair Information Company, LLC

Sunday, March 19, 2000 12:41AM

Condition			3	Code	3	Procedure
Attaching hardware broken			3	A	3	Require replacement of broken part, if available; otherwise, replace trailing arm.
Attaching hardware loose			3	A	3	Require repair or replacement of loose part, if available; otherwise, replace trailing arm.
Attaching hardware missing			3	C	3	Require replacement of missing part, if available; otherwise, replace trailing arm.
Attaching hardware threads damaged			3	A	3	Require repair or replacement of part with damaged threads, if available; otherwise, replace trailing arm.
Attaching hardware threads stripped (threads missing)			3	A	3	Require replacement of part with stripped threads, if available; otherwise, replace trailing arm.
Bent			3	B	3	Require replacement.
Bushing hole oversized			3	B	3	Require replacement.
Corroded, affecting structural integrity			3	A	3	Require replacement.
Holes distorted			3	A	3	Require replacement.
Threads damaged			3	A	3	Require repair or replacement.
Threads stripped (threads missing)			3	A	3	Require replacement.

WHEEL ALIGNMENT

WHEEL ALIGNMENT

Wheel alignment is defined as the measurement, analysis, and adjustment of steering and suspension angles to conform to OEM specifications. These angles usually include, but are not limited to: caster, camber, toe, and thrust angle. Where these angles are not adjustable and not in specification, component replacement or correction kits may be required. Errors in set-back and steering axis inclination (SAI) are often attributable to failed or damaged components and must be corrected prior to performing an alignment.

Failure to replace or correct suggested or required parts or

WHEEL BEARINGS, RACES, & SEALS

*** SUSPENSION UNIFORM INSPECTION GUIDELINES ***

Article Text (p. 60)

1987 Volkswagen Quantum/Quantum Syncro

For Volkswagen Technical Site

Copyright © 1998 Mitchell Repair Information Company, LLC

Sunday, March 19, 2000 12:41AM

Condition			3	Code	3	Procedure
Rear axle seal on rear-wheel drive leaking			3	A	3	Require replacement of seal and inspection of axle, bearing, housing, and vent tube
Seal bent			3	A,1	3	Suggest replacement.
Seal leaking			3	A	3	Require replacement of seal and inspection of bearings.
Seal missing			3	C	3	Require replacement.
Seal torn			3	A	3	Require replacement.
Wheel bearing assembly feels rough when rotated			3	A	3	Require replacement of bearing assembly.
Wheel bearing balls are pitted			3	A	3	Require replacement of bearing assembly.
Wheel bearing balls are worn			3	A	3	Require replacement of bearing assembly.
Wheel bearing end-play exceeds vehicle manufacturer's specs			3	A	3	Require adjustment of bearing, if possible. If proper adjustment cannot be obtained, require repair or replacement of worn component.
Wheel bearing race is loose in the hub bore			3	A	3	Require replacement of hub assembly and wheel bearings.
Wheel bearing races are pitted			3	A	3	Require replacement of bearing assembly.
Wheel bearing races are worn			3	A	3	Require replacement of bearing assembly.
Wheel bearing rollers are pitted			3	A	3	Require replacement of bearing assembly.
Wheel bearing rollers are worn			3	A	3	Require replacement of bearing assembly.

WHEELS & TIRES

TIRES

WARNING: These guidelines do not apply to split rims.

*** SUSPENSION UNIFORM INSPECTION GUIDELINES ***

Article Text (p. 61)

1987 Volkswagen Quantum/Quantum Syncro

For Volkswagen Technical Site

Copyright © 1998 Mitchell Repair Information Company, LLC

Sunday, March 19, 2000 12:41AM

Some vehicle manufacturers restrict replacement of tires to specific brands, types, or sizes.

High pressure temporary compact spare tires should not be used with any other rims or wheels, nor should standard tires, snow tires, wheel covers, or trim rings be used with high pressure compact spare rims or wheels.

Attempting to mount a tire of one diameter on a wheel of a different diameter or flange type may result in serious injury or death.

Only specially trained persons should de-mount or mount tires. Explosions of tire and wheel assembly can result from improper mounting, possibly causing serious injury or death.

Consult the vehicle owner's manual or vehicle placard for correct size, speed rating, designation, and cold inflation pressure of the original tires. DO NOT exceed the maximum load or inflation capacity of the tire specified by the Tire and Rim Association

When replacing tires, it is suggested that the replacement tires match or exceed the OEM speed rating designation. If tires of different speed rating designations are mixed on the same vehicle, the tires may vary in handling characteristics. DO NOT mix different speed rating designations on the same axle.

DO NOT mix radials with non-radial tires on the same axle, as this may affect vehicle handling and stability. If radial tires and bias or bias-belted ply tires are mixed on the same vehicle, the radials must be on the rear. High-pressure temporary compact spare tires are exempt from this rule.

DO NOT mix size or type (all season, performance, mud and snow) of tires on the same axle.

TIRES

Condition			Code	Procedure
Air pressure incorrect				
			B	Require repair
Bead broken				
			A	Require replacement.
Bead leaking, caused by tire				
			A	Require repair or replacement.
Bead wire/cord exposed				
			A	Require replacement.
Cord or belt material exposed				
			A	Require replacement.
Cord ply separations				
			A	Require replacement.
Directional/asymmetrical tires mounted incorrectly				
			B	Require remounting and/or repositioning.
Irregular tread wear, affecting performance				
			A	Suggest replacement.
				See note (1) below.
Load ratings less than OEM				
			B	Require replacement.

*** SUSPENSION UNIFORM INSPECTION GUIDELINES ***

Article Text (p. 62)

1987 Volkswagen Quantum/Quantum Syncro

For Volkswagen Technical Site

Copyright © 1998 Mitchell Repair Information Company, LLC

Sunday, March 19, 2000 12:41AM

specifications	3	3	
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA			
Mixed tire size designations	3	A	3 Require rotation or
on same axle	3	3	replacement.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA			
Mixed tread types (all season,	3	A	3 Require rotation or
performance, mud and snow)	3	3	replacement.
on same axle	3	3	
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA			
Number of punctures exceeds	3	B	3 Require replacement.
manufacturer's limit	3	3	
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA			
Out of balance	3	B	3 Require rebalance of tire/wheel
	3	3	assembly.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA			
Ply separation	3	A	3 Require replacement.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA			
Pull or lead, caused by tire	3	A	3 Require rotation or
	3	3	replacement.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA			
Radial and bias or bias-belted	3	B	3 Require rotation or
ply tires on same axle	3	3	replacement.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA			
Radials are on the front and	3	B	3 Require rotation or
not on the rear	3	3	replacement. See note (2).
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA			
Run flat damage	3	A	3 Require replacement.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA			
Shoulder cut	3	A	3 Require replacement.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA			
Shoulder puncture	3	A	3 Require replacement.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA			
Shoulder with plug	3	A	3 Require replacement.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA			
Sidewall bulge	3	A	3 Require replacement.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA			
Sidewall cut	3	A	3 Require replacement.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA			
Sidewall indentation	3		3 No service required/suggested.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA			
Sidewall puncture	3	A	3 Require replacement.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA			
Sidewall with plug	3	A	3 Require replacement.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA			
Speed rating designations	3	B	3 Suggest rotation or
different on same axle	3	3	replacement.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA			
Tire and wheel assembly has	3	B	3 Require repair or replacement
excessive run-out	3	3	of appropriate part. See note
	3	3	(3) below.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA			
Tires with more than 1/4"	3	B	3 Require replacement.

*** SUSPENSION UNIFORM INSPECTION GUIDELINES ***

Article Text (p. 63)

1987 Volkswagen Quantum/Quantum Syncro

For Volkswagen Technical Site

Copyright © 1998 Mitchell Repair Information Company, LLC

Sunday, March 19, 2000 12:41AM

diameter difference on a	3	3	
four-wheel drive vehicle	3	3	
Tread area puncture larger in 3 B 3 Require replacement.			
diameter than tire	3	3	
manufacturer's specifications	3	3	
Tread missing pieces 3 A 3 Require replacement.			
(chunking), exposing cord	3	3	
Tread missing pieces 3 A 3 Suggest replacement.			
(chunking), not exposing cord	3	3	
Tread separations 3 A 3 Require replacement.			
Tube in tubeless tire 3 C,3 3 Suggest removal of tube.			
	3	3	See note (4) below.
Weather-checking 3 3 No service required/suggested.			
Worn to tread wear indicators 3 B 3 Require replacement.			

NOTE: (1) Determine and correct cause of irregular tire wear.
(2) If radials and bias or bias-belted ply tires are on the same vehicle, the radials must be on the rear axle, except for high-pressure temporary spares.
(3) Excessive is defined as enough to contribute to performance problems. Match mounting may correct run-out. If not, require replacement of appropriate part. Refer to manufacturer's specifications.
(4) Most manufacturers do not recommend tubes in tubeless tires. Inspect tire and wheel assembly to determine the reason for a tube in tubeless tire. Recommendation for repair or replacement should be based upon condition of tires and/or wheel listed in these guidelines.

VALVE STEMS

VALVE STEMS			
Condition	3	Code	3 Procedure
Bent 3 A,1 3 Suggest replacement.			
Broken 3 A 3 Require replacement.			
Cut, but not leaking 3 A,1 3 Suggest replacement.			
Deteriorated (cracking, dry rot) 3 A,1 3 Suggest replacement.			
Leaking 3 A 3 Require repair/replacement.			

Sunday, March 19, 2000 12:41AM

Condition	Code	Procedure
Bent	A	Require replacement.
Broken	A	Require replacement.
		See note (1) below.
Loose	B	Require repair or replacement
		of affected component.
Lug nut installed backward	B	Require repair.
Lug nut mating type incorrect	B	Require replacement of nut.
Lug nut mating surface dished	A	Require replacement of nut.
Lug nut flats rounded	A	Require replacement of nut.
		See note (2) below.
Lug nut seized	A	Require replacement of nut
		and/or stud. See note (2) below.
Stud incorrect	B	Require replacement of stud.
Threads damaged	A	Require repair or replacement of
		component with damaged threads.

*** SUSPENSION UNIFORM INSPECTION GUIDELINES ***

Article Text (p. 65)

1987 Volkswagen Quantum/Quantum Syncro

For Volkswagen Technical Site

Copyright © 1998 Mitchell Repair Information Company, LLC

Sunday, March 19, 2000 12:41AM

Threads stripped (threads 3 A 3 Require replacement of

missing) 3 3 component with stripped threads.

NOTE: (1) Some manufacturers require replacement of all studs on that
wheel if two or more studs or nuts on the same wheel are
broken or missing.

(2) Only required if removing wheel.

WHEELS

WARNING: Mounting a regular tire on a high-pressure compact spare
wheel is not permitted. Attempting to mount a tire of one
diameter on a wheel of a different diameter or flange type
may result in serious injury or death. If the wheel
identification stamp is not legible, or cannot be found,
DO NOT use the wheel until the size and type have been
properly identified. Wheels of different diameter, offset,
or width cannot be mixed on the same axle. Bead seat tapers
cannot be interchanged.

WHEELS

Condition 3 Code 3 Procedure

Bead leaking, caused by 3 A 3 Require repair or replacement.
wheel rim flange 3 3 See caution below.

CAUTION: DO NOT attempt to correct a bent wheel rim.

Bent wheel hub mounting 3 A 3 Require replacement.
surface 3 3

Bent wheel rim, causing 3 B,2 3 Suggest replacement.
vibration 3 3 See caution above.

Broken 3 A 3 Require replacement.

Cast wheel porous, causing 3 A 3 Require repair or replacement.
a leak 3 3

Clip-on balance weight is 3 B,2 3 Suggest replacement.
incorrect type for wheel 3 3
rim flange 3 3

Corrosion, affecting 3 A 3 Require replacement.
structural integrity 3 3

Corrosion build-up on wheel 3 A 3 Require repair.
hub mounting surface 3 3

*** SUSPENSION UNIFORM INSPECTION GUIDELINES ***

Article Text (p. 66)

1987 Volkswagen Quantum/Quantum Syncro

For Volkswagen Technical Site

Copyright © 1998 Mitchell Repair Information Company, LLC

Sunday, March 19, 2000 12:41AM

Cracked 3 A 3 Require replacement.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
Directional/asymmetrical 3 B 3 Require remounting and/or
wheels mounted incorrectly 3 3 repositioning.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
Load capacity less than 3 B 3 Require replacement.
OEM specifications 3 3
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
Offset mismatched on same 3 B 3 Require replacement.
axle 3 3
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
Rivets leaking 3 A 3 Require replacement.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
Run-out beyond OEM specs 3 B 3 Require replacement.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
Stud holes elongated 3 A 3 Require replacement. See note (1)
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
Welded or brazed repair 3 B,2 3 Suggest replacement.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
Welds leaking 3 A 3 Require replacement.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
Wheel hub centering (pilot) 3 B 3 Require replacement.
hole incorrect 3 3
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
NOTE: (1) Inspect wheel attaching hardware for damage.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

END OF ARTICLE