

# ANTI-LOCK BRAKE SAFETY PRECAUTIONS

## Article Text

1993 Volkswagen Passat

For Volkswagen Technical Site: <http://vw.belcom.ru>

Copyright © 1998 Mitchell Repair Information Company, LLC

Wednesday, March 22, 2000 10:02PM

## ARTICLE BEGINNING

### GENERAL INFORMATION

#### Anti-Lock Brake Safety Precautions

#### \* PLEASE READ THIS FIRST \*

This article is intended for general information purposes only. This information may not apply to all makes and models. If vehicle is equipped with Anti-Lock Brake System (ABS), refer to appropriate ANTI-LOCK BRAKE SYSTEM article in the BRAKES section for description, operation, depressurizing, testing, system bleeding, trouble shooting and servicing of specific system.

WARNING: Failure to depressurize ABS could lead to physical injury.

## ANTI-LOCK BRAKE SAFETY PRECAUTIONS

WARNING: Failure to depressurize ABS could lead to physical injury.

- \* NEVER open a bleeder valve or loosen a hydraulic line while ABS is pressurized.
- \* NEVER disconnect or reconnect any electrical connectors while ignition is on. Damage to ABS control unit may result.
- \* DO NOT attempt to bleed hydraulic system without first referring to the appropriate ANTI-LOCK BRAKE SYSTEM article in the BRAKES section.
- \* Only use specially designed brake hoses/lines on ABS equipped vehicles.
- \* DO NOT tap on speed sensor components (sensor, sensor rings). Sensor rings must be pressed into hubs, NOT hammered into hubs. Striking these components can cause demagnetization or a loss of polarization, affecting the accuracy of the speed signal returning to the ABS control unit.
- \* DO NOT mix tire sizes. Increasing the width, as long as tires remain close to the original diameter, is acceptable. Rolling diameter must be identical for all 4 tires. Some manufacturers recommend tires of the same brand, style and type. Failure to follow this precaution may cause inaccurate wheel speed readings.
- \* DO NOT contaminate speed sensor components with grease. Only use recommended coating, when system calls for an anti-corrosion coating.
- \* When speed sensor components have been removed, ALWAYS check sensor-to-ring air gaps when applicable. These specifications can be found in each appropriate article.
- \* ONLY use recommended brake fluids. DO NOT use silicone brake fluids in an ABS equipped vehicle.
- \* When installing transmission devices (CB's, telephones, etc.) on ABS equipped vehicles, DO NOT locate the antenna near the ABS control unit (or any control unit).

## **ANTI-LOCK BRAKE SAFETY PRECAUTIONS**

### **Article Text (p. 2)**

1993 Volkswagen Passat

For Volkswagen Technical Site: <http://vw.belcom.ru>

Copyright © 1998 Mitchell Repair Information Company, LLC

Wednesday, March 22, 2000 10:02PM

- \* Disconnect all on-board computers, when using electric welding equipment.
- \* DO NOT expose the ABS control unit to prolonged periods of high heat (185 °F/85°C for 2 hours is generally considered a maximum limit).

**END OF ARTICLE**